

UNIVERSITY OF KERALA Thiruvananthapuram, Kerala, India – 695034 (Established as University of Travancore by the Travancore University Act in1937 and reconstituted as University of Kerala by the Kerala University Act of 1957 and presently governed by the Kerala University Act of 1974 passed by the Kerala State Legislative Assembly)

No. Ad. B IV.CP.01.599.2017

Thiruvananthapuram Dated: 24.03.2017

## **QUOTATION NOTICE**

Competitive Quotations are invited for the supply of one Semi Automatic Strapping Machine for use in the CVC I & CVC II Sections in the Examination Wing of the University Office.

## **Conditions**

- 1. The rate quoted should be inclusive of Tax, transportation charges and any other charges.
- 2. Complaints with the items supplied should be rectified/replaced to the satisfaction of the University by the suppliers at their own cost.
- 3. Payment will be made only after the supply of the items at our own site.
- 4. The undersigned reserves the right to reject /accept any quotation without assigning any reason.

The sealed quotations should be addressed to the undersigned super scribing as Quotations for the supply of one Semi Automatic Strapping Machine for use in the CVC I & CVC II Sections in the Examination Wing of the University Office.. The last date of receipt of quotations is at 3.00 PM on 03.04.2017. The quotations will be opened at 3.30 PM on the same day in the presence of vendors then present.

Sd/-REGISTRAR

## **Specifications**

## **Features**

- Instant Heating in only 20 seconds
- Durable electro-magnetic clutch transmission increases motor life, strapping speed & reduce overall noise.
- The unique design of control switch independent PCB control for feeding & healing make the unit maintenance friendly.
- One touch machine operation energy saving mode activates within 1.5 seconds of non-use and allows for install opeation

Model	FB90/ FB90L
Strapping Speed	1.5 second/strap
Strapping Force	60 kg
Strap Width	9.15 mm
Power supply &	220 Vm 50/60 Hz, 0.65 KW, Single Phase
Consumption	
Dimension (mm)	895 x 565 x 735 (LxWxH)
Weight	90 kg