UNIVERSITY OF KERALA ENGINEERING UNIT, KARIAVATTOM

TENDER SCHEDULE FOR IMPLIMENTATION OF IT TRAINING CENTRE AND SOFTWARE DEVELOPMENT CENTRE BUILDING AT SH CAMPUS TRIVANDRUM- ELECTRIFICATION AND BIOMETRIC LOCK SYSTEM.

| Sl.No | Qty | Specification | Rate | Rate in words | Unit | Amount |
|-------|-----|---|---------|--|------|---------|
| 1/122 | | Supply and wiring points according to IS 732-1989 using | | | | |
| | | rigid PVC ivory conduit of minimum size 20 mm | | | | |
| | | conforming to IS 9537 part III 1983 and with suitable size | | | | |
| | | specials conforming to IS 3419-1988, fixing the conduit | | | | |
| | | using metal saddles spacing not exceeding 50 cm or | | | | |
| | | concealed suitably and with 1.00 sq mm PVC insulated | | | | |
| | | stranded single core FR copper conductor cable 650V | | | | |
| | | grade,including providing switch board main ,and | | | | |
| | | continuous earthing with 1.5sqmm green coloured FR wire, | | | | |
| | | required qty of copper earth socket, brass bolt and nut | | | | |
| | | crimping etc complete with suitable size modular type metal | | | | |
| | | switch boxes, modular type front plates (white) etc. up to | | | | |
| | | and including 6 A modular typeROHS compliant SP | | | | |
| | | switches and making good the surface of wall, colour | | | | |
| | | washing etc. complete. All the terminations in the switch | | | | |
| | | boards and DB's shall be tinned and the wires shall be | | | | |
| | | drawn and fixed along the periphery of the box using | | | | |
| | | suitable ties, tie mounts etc as required. | | | | |
| B1 | 10 | Single control light point with 6A, 3 plate ceiling rose | 966.00 | Rs. Nine hundred and sixty six only | E | 9660.00 |
| B4 | 5 | Single control light point without ceiling rose | 946.00 | Rs. Nine hundred and forty six only | E | 4730.00 |
| В6 | 4 | Single control ceiling fan point with 6 A, 3 plate ceiling | 1622.00 | Rs. One thousand six hundred and | Е | 6488.00 |
| | | rose & with socket size stepped electronic regulator. | | twenty two only | | |
| В8 | 3 | Combined plug point with 6 A, 5 pin plug socket controlled | 483.00 | Rs. Four hundred and eighty three only | Е | 1449.00 |
| | | by 6 A switch in the same switch board as that of light | | | | |
| | | points. | | | | |

| 2/206 | 22 | Supplying and providing <i>extra steel chain</i> (16 SWG) 2 <i>x</i> 1.00 <i>m</i> long with 16/0.20 mm 3 core copper conductor flex wire conforming to relevant ISS or with the extended original wiring and giving connection etc. as required. | 207.00 | Rs. Two hundred and seven only | Е | 4554.00 |
|-------|----|--|---------|---|---|-----------|
| 3/208 | 2 | Conveyance, installation, testing and commissioning of prewired light fittings of all types complete with all accessories and fluorescent lamps etc. including supplying and fixing ball and socket arrangements on T.W round block, suspension down rod of 19 mm dia MS conduit up to 2x30cm length including painting and wiring the down rod with 16/0.20mm 3 core round copper conductor flex wire conforming to relevant ISS or extending the original wiring and giving connections etc. a required. | 371.00 | Rs. Three hundred and seventy one only | E | 742.00 |
| 4/229 | | Supply, conveyance, installation, testing and commissioning of pre-wired fitting made of CRCA sheet .5mm thick with all accessories and lamps etc. suspended from ceiling using 2 nos steel chain of length not exceeding 30 cm properly hooked to steel hooks anchored to the ceiling and giving connections with required length of 16/0.20mm 3 core copper conductor flex wire conforming to relevant ISS or extending the original wiring and giving connection etc. as required. | | | | |
| Е | 21 | Recess mounting decorative fluorescent tube (cat2)light fitting complete with lamp holder, APF electronic ballast suitable for continuous operation with THD <10%, power factor >0.98, RoHS compliant,high lumen tube, duly wired up for use on 230 V AC supply. Suitable for 4 Nos 14 W T5 lamps | 7058.00 | Rs. Seven thousand and fifty eight only | E | 148218.00 |
| 5/240 | 4 | Supply and fixing angle / straight brass lined skirt type, bakelite batten holder without shade and giving connection etc as required | 63.00 | Rs. sixty three only | Е | 252.00 |
| 6/244 | | Supply and fixing cast aluminium stove enameled bulk head fitting with deep drawn anodised aluminium body, epoxy | | | | |

| | | powder coated, heat resistant prismatic glass cover suitable | | | | |
|--------|-----|---|---------|--------------------------------------|---|----------|
| | | for 9 W CFL to wall / ceiling including giving connections | | | | |
| | | with required length of 16/0.20mm PVC insulated and PVC | | | | |
| | | sheathed 3 core round copper conductor flex wire | | | | |
| | | conforming to relevant ISS or extending the original wiring | | | | |
| | | and making good the surface as required. | | | | |
| | 4 | Normal size 11 W BC / ES retrofit CFL | 156.00 | Rs. One hundred and fifty six only | Е | 624.00 |
| 7 | 1 | Charges for cutting holes suitable for accommodating | 294.00 | Rs. Two hundred and ninty four only | Е | 294.00 |
| | | exhaust fans of sizes up to 305 mm sweep including | | | | |
| | | plastering, colour washing etc. as required. | | | | |
| 8/313 | | Supply, conveyance, installation, testing and commissioning | | | | |
| | | of the following sizes of exhaust fans in the existing | | | | |
| | | opening, fixing necessary bolt and nuts, making good the | | | | |
| | | damages etc. as required including giving connections with | | | | |
| | | required length of 24/0.20mm PVC insulated and PVC | | | | |
| | | sheathed 3 core round copper conductor flex wire | | | | |
| | | conforming to relevant ISS. | | | | |
| | 1 | 300/ 305 mm, single phase light duty exhaust fan in metal | 1828.00 | Rs. One thousand eight hundred and | Е | 1828.00 |
| | | frame | | twenty eight only | | |
| 9/330 | | Supply and fixing the following sizes of <i>PVC Conduit</i> | | | | |
| | | conforming to IS 9537 / 1983 part III along with all required | | | | |
| | | accessories on surface including making good the damages | | | | |
| | | etc as required. | | | | |
| B1 | 150 | 20 mm dia medium gauge | 87.00 | Rs. Eighty seven only | M | 13050.00 |
| B2 | 50 | 25 mm dia medium gauge | 99.00 | Rs. Ninty nine on ly | M | 4950.00 |
| 10 | | Supply and fixing the following sizes of <i>PVC Conduit</i> | | | | |
| | | conforming to IS 9537 / 1983 part III along with all required | | | | |
| | | accessories in recess including cutting the wall and making | | | | |
| | | good the damages etc as required. | | | | |
| B1 | 50 | 20 mm dia medium gauge | 124.00 | Rs. One hundred and twenty four only | M | 6200.00 |
| B2 | 10 | 25 mm dia medium gauge | 136.00 | Rs. One hundred and thirty six only | M | 1360.00 |
| 11/333 | | Supplying and clamping the following sizes of <i>corrugated</i> | | | | |
| | | PVC flexible conduit with necessary compression gland | | | | |
| | | with locking ring and check nut at termination pointed using | | | | |

| | | suitable size GI / painted MS saddles spacing not exceeding 60 cms on surface including making good the damages, | | | | |
|--------|-----|--|--------|--------------------------------------|---|----------|
| | | colour washing etc. as required. | | | | |
| a | 10 | 16 mm dia | 48.00 | Rs. Fourty eight only | M | 480.00 |
| 12/340 | | Supply and drawing 650/1100 V grade PVC insulated | | | | |
| | | stranded single core copper conductor cables conforming to | | | | |
| | | IS 694 part I 1990 in the existing surface / recess conduit as | | | | |
| | | required including giving necessary connections of the | | | | |
| | | following sizes. | | | | |
| | 50 | 1.50 sq mm 2 run | 61.00 | Rs. sixty one only | M | 3050.00 |
| | 100 | 1.50 sq mm 4 run | 94.00 | Rs. Ninty four only | M | 9400.00 |
| | 150 | 2.50 sq mm 1 run | 55.00 | Rs. Fifty five only | M | 2250.00 |
| | 100 | 2.50 sq mm 2 run | 81.00 | Rs. Eighty one only | M | 8100.00 |
| | 100 | 2.50 sq mm 3 run | 107.00 | Rs. One hundred and seven only | M | 10700.00 |
| | 50 | 2.50 sq mm 4 run | 134.00 | Rs. One hundred and thirty four only | M | 6700.00 |
| | 15 | 4.00 sq mm 2 run | 106.00 | Rs. One hundred and six only | M | 1590.00 |
| | 20 | 4.00 sq mm 4 run | 134.00 | Rs. One hundred and thirty four only | M | 2680.00 |
| | 10 | 6.00 sq mm 2 run | 144.00 | Rs. One hundred and forty four only | M | 1440.00 |
| 13/343 | | Supplying & Drawing the following types of <i>UTP Cable</i> | | | | |
| | | conforming to relevant standards through the existing | | | | |
| | | conduit and giving connections as required | | | | |
| b | 700 | Cat 6 UTP Cable | 52.00 | Rs. Fifty two only | M | 36400.00 |
| 14/350 | | Supplying and fixing the following sizes of M.S. Boxes | | | | |
| | | made out of 1.60 mm thick sheet painted grey (both inside | | | | |
| | | and outside) in surface/ recess including phenolic | | | | |
| | | laminated sheet covers of thicknesses noted along with | | | | |
| | | screwed to the box as front cover with steel screws, cup | | | | |
| | | washers etc. making good the surface, painting /colour | | | | |
| | | washing etc. as required. | | | | |
| C19 | 4 | 200x150x 50mm with 3 mm sheet | 317.00 | Rs. Three hundred and seventeen only | Е | 1268.00 |
| C20 | 3 | 250X200x 50mm with 3 mm sheet | 413.00 | Rs. Four hundred and thirteen only | Е | 1239.00 |
| 15/360 | | Supplying and fixing the following <i>piano type accessories</i> | | | | |
| | | in the phenolic laminated front cover of existing MS box | | | | |

| | | including providing necessary holes and giving connections | | | | |
|--------|-----|---|--------|---------------------------------------|---|----------|
| | | etc. as required. | | | | |
| A1 | 40 | 6A 1 way switch | 47.00 | Rs. Forty seven only | E | 1880.00 |
| D4 | 10 | 6 A 3 pin socket | 53.00 | Rs. Fifty three only | Е | 530.00 |
| S3 | 10 | 100 W Step type fan regulator - 2 M | 522.00 | Rs. Five hundred and twenty two only | Е | 5220.00 |
| 16/385 | | Supply & Fixing the following types/ sizes of boxes suitable | | | | |
| | | for modular accessories in surface/ recess including making | | | | |
| | | good the damages, colour washing etc as required (ROHS) | | | | |
| A3 | 54 | 1 module moulded plastic box on surface | 185.00 | Rs. One hundred and eighty five only | Е | 9990.00 |
| A5 | 15 | 6 module moulded plastic box on surface | 209.00 | Rs. Two hundred and nine only | Е | 3135.00 |
| A6 | 4 | 8 module moulded plastic box on surface | 233.00 | Rs. Two hundred and thirty three only | Е | 932.00 |
| В3 | 2 | 3 module metal box in recess | 194.00 | Rs. One hundred and ninty four only | Е | 388.00 |
| C3 | 17 | 12 module metal box in recess | 269.00 | Rs. Two hundred and sixty nine only | Е | 4578.00 |
| 17 | | Supply & Fixing the following types/ sizes of front plates | | | | |
| | | on the existing modular boxes. (RoHS) | | | | |
| C9 | 54 | 1 module white/ off-white | 101.00 | Rs. One hundred and one only | Е | 5454.00 |
| C11 | 2 | 3 module white/ off-white | 116.00 | Rs. One hundred and sixteen only | Е | 232.00 |
| A12 | 15 | 6 module white/ off-white | 152.00 | Rs. One hundred and fifty two only | Е | 2280.00 |
| A13 | 4 | 8 module white/ off-white | 187.00 | Rs. One hundred and eighty seven | Е | 748.00 |
| | | | | only | | |
| B2 | 17 | 12 module white/ off-white | 251.00 | Rs. Two hundred and fifty one only | Е | 4267.00 |
| 18 | | Supply and Fixing the following modular switches & | | | | |
| | | accessories in the existing front plates and giving necessary | | | | |
| | | connections as required (RoHS) | | | | |
| C4 | 60 | 6 A SP 1 way switch | 119.00 | Rs. One hundred and nineteen only | Е | 7140.00 |
| B2 | 1 | 16 A SP 1 way switch | 161.00 | Rs. One hundred and sixty one only | Е | 161.00 |
| G2 | 110 | 6A 3 pin shuttered socket | 157.00 | Rs. One hundred and fifty seven only | Е | 17270.00 |
| H2 | 1 | 6/16 A socket | 223.00 | Rs. Two hundred and twenty three | Е | 223.00 |
| | | | | only | | |
| I5 | 54 | RJ45 | 119.00 | Rs. One hundred and nineteen only | Е | 6426.00 |
| 19 | | Supply and installation of sheet steel, phosphatised and | | | | |
| | | painted, dust and vermin proof enclosure of MCB DB | | | | |
| | | including copper /brass bus bar, neutral link, earth bus and | | | | |
| | | DIN rail suitable for fixing MCB/ isolator etc. fixed on wall | | | | |

| | | using suitable anchor bolts or fixed in recess including cutting hole on the wall, making good the damages, colour | | | | |
|--------|----|--|----------|--|---|----------|
| | | washing etc. as required | | | | |
| T10 | 4 | DP enclosure for independent mounting of MCB | 486.00 | Rs. Four hundred and eighty six only | Е | 1944.00 |
| T12 | 4 | FP enclosure for independent mounting of MCB/ RCCB/ RCBO | 604.00 | Rs. Six hundred and four only | Е | 2416.00 |
| A1 | 2 | 12 way single phase double cover (IP 42/43) | 1899.00 | Rs. One thousand eight hundred and ninty nine only | Е | 3798.00 |
| F3 | 1 | 6 way (8+18) - double cover TPN vertical DB with provision for fixing MCCB as incomer and SP/ TP MCB as outgoing (IP 42/43) (direction from department) | 10124.00 | Rs. Ten thousand one hundred and twenty four only | Е | 10124.00 |
| 20 | | Supply and installation of the following <i>accessories</i> suitable for 50 Hz, AC supply conforming to IS 8828-1995/ IEC 60898 of the following current ratings in the existing enclosure and giving connections as required | | | | |
| N5 | 2 | 40 A, 2 pole, 30 mA RCCB | 2357.00 | Rs. Two hundred and three hundred and fifty seven only | Е | 4714.00 |
| I3 | 2 | 40 A double pole mini break isolator | 356.00 | Rs. Three hundred and fifty six only | Е | 712.00 |
| J3 | 3 | 40 A triple pole mini break isolator | 568.00 | Rs. Five hundred and sixty eight only | Е | 1704.00 |
| K3 | 1 | 63 A four pole mini break isolator | 752.00 | Rs. Seven hundred and fifty two only | Е | 752.00 |
| V3 | 8 | 6-32A(C curve)SP MCB (C curve) | 219.00 | Rs. Two hundred and nineteen only | Е | 1752.00 |
| 21 | | Supply, laying and clamping of 1 no. PVC insulated and PVC sheathed armoured aluminium power cable, 1.1 KV grade of the following sizes using clamps noted along with the cables, spacing of clamps not exceeding 60cms, making good the damages, colour washing etc. as required. | | | | |
| | 20 | 4 core 25 sq mm with factory made clamp | 281.00 | Rs. Two hundred and eighty one only | M | 5620.00 |
| | 20 | 4c core 50 sq mm with factory made clamp | 435.00 | Rs. Four hundred and thirty five only | M | 8700.00 |
| 22/686 | | Supply of superior quality <i>aluminium reducer</i> (banana) cable socket and making core termination of cables of the following sizes including crimping etc. as required. | | | | |
| a | 8 | 25 sq mm | 22.00 | Rs. Twenty two only | Е | 176.00 |
| С | 8 | 50 sq mm | 31.00 | Rs. Thirty one only | Е | 248.00 |
| 23 | | Supply and drawing bare earthing conductors of the | | | | |

| | | following sizes along with wiring/ cables and giving | | | | |
|--------|-----|--|----------|---|----|-------------|
| | | connection as required. | | | | |
| C1 | 100 | 2.00 mm copper conductor (14 SWG) | 26.00 | Rs. Twenty six only | M | 2600.00 |
| C2 | 20 | 2.65 mm copper conductor (12 SWG) | 43.00 | Rs. Forty three only | M | 860.00 |
| 24/826 | | Supply, conveyance and fixing the following types & current rated control gears & switchgears conforming to IS 13947 suitable for 440 V, 50 Hz, AC supply in the existing panel assembly as required | | | | |
| A2 | 1 | 10/ 25/ 63/ 100A, 35/36 kA (Ics=100%Icu), 4 pole, current limiting type MCCB with microprocessor based release with overload setting of 50 - 100% having adjustable OL & SC | 12659.00 | Rs. Twelve thousand six hundred and fifty nine only | Е | 12659.00 |
| 1 | | Charges for dismantling existing DB ,old fittings such as switches switch boards unnecessary wires etc | | | LS | 4195.00 |
| 2 | | Supplying, installation testing and commissioning of biometric lock system | | | LS | 30000.00 |
| | | Tota | ıl | | | 4,53,524.00 |

PAC Rs.453524/- (Rs. Four lakh fifty three thousand five hundred and twenty four only)

2. percentage below the estimate rate 3. At the estimate rate.

UNIVERSITY ENGINEER CONTRACTOR